

SB4132SM_400V // drill press



highlights

- left/right rotation 2- step motor
- speed range 60-3480min-1
- features solid, polished base with T-nuts
- aluminum motor according IP54
- torsion-resistant, solid and polished steel column
- the worktable is tiltable from -45° to +45° and rotates 360° around table center and column
- spindle protection cover
- adjustable drill depth stop with scale for accurate drill depth control
- selection switch for CW/CCW-rotation
- 2-step motor

included in delivery: automatic chuck 1-16mm, B18



1.099,00

SB4132SM_400V // drill press



technical details

| | |
|-----------------------------|---------------|
| motor power s6 in W | 1500/2200 |
| voltage | 400V |
| table size in mm | 475x420 |
| max. height in mm | 1710 |
| base in mm | 580x450 |
| distance spindle-base in mm | 1160 |
| drilling spindle collet | MK4 / MT4 |
| column diameter in mm | 90 / 2,5 |
| gross weight in kg | 125 |
| packaging width in mm | 653 |
| EAN code | 9120039901961 |

| | |
|-----------------------------------|--------------|
| motor power s1 in W | 700/1100 |
| total dimensions in mm | 570x870x1710 |
| outreach in mm | 257 |
| max. drilling performance in mm | 32 |
| spindle stroke in mm | 120 |
| max. distance spindle-table in mm | 680 |
| drilling spindle speed in min-1 | (24) 60-3480 |
| net weight in kg | 120 |
| packaging height in mm | 333 |
| packaging length in mm | 1.450 |